

# SET-XP® High Strength Anchoring Adhesive for Cracked and Uncracked Concrete

## SAFETY DATA SHEET



### 1. Identification

#### Product Identification

**Product Identifier:** SET-XP (SET-XP10, SET-XP22, SET-XP56, SET-XP650, SET-XP)  
**Recommended Use:** High Strength Anchoring Adhesive for Cracked and Uncracked Concrete  
**Use Restrictions:** None Known.

#### Company Identification

**Company:** Simpson Strong-Tie Company Inc.  
**Address:** 5956 W. Las Positas Blvd.  
Pleasanton, CA 94588  
**Phone:** 1-800-999-5099  
**Website:** www.strongtie.com  
**Emergency:** 1-800-535-5053 (US/Canada) / 1-352-323-3500 (International)  
For most current SDS, please visit our website at [www.strongtie.com/sds](http://www.strongtie.com/sds)

### 2. Hazard Identification

#### General Information

SET-XP Anchoring Adhesive is a two part system. The two parts of this product have been assessed according to GHS and are classified below. The final hardened material is considered nonhazardous. Some hazards apply upon grinding or cutting through hardened product.

#### Resin (white side) GHS Classification



<b>Physical Hazards:</b>	Not Classified.	
<b>Health Hazards:</b>	Skin Corrosion/Irritation	Category 2
	Serious Eye Damage/Irritation	Category 2A
	Sensitization, Skin	Category 1
	Germ Cell Mutagenicity	Category 2
<b>Environmental Hazards:</b>	Chronic Aquatic Environmental Hazard	Category 2

**Signal Word:** **WARNING!**  
**Hazard Statements:** Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing genetic defects. Toxic to aquatic life with long lasting effects.

**Precautionary Statements:**  
**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace. Avoid breathing mist or vapor. Wash thoroughly after handling. Avoid release to the environment.  
**Response:** If exposed or concerned: Call a poison center/doctor. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before re-use. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Collect Spillage.  
**Storage:** Store locked up. Store in a well-ventilated place. Store between 45-90°F (7-32°C).  
**Disposal:** Dispose of contents/container in accordance with local/regional/national regulations.

#### Hardener (green side) GHS Classification



<b>Physical Hazards:</b>	Not Classified.	
<b>Health Hazards:</b>	Skin Corrosion/Irritation	Category 1
	Serious Eye Damage/Irritation	Category 1
	Sensitization, Skin	Category 1

**SET-XP® High Strength Anchoring Adhesive for Cracked and Uncracked Concrete**  
SAFETY DATA SHEET



**Environmental Hazards:** Germ Cell Mutagenicity Category 2  
Acute Aquatic Environmental Hazard Category 3  
Chronic Aquatic Environmental Hazard Category 3

**Signal Word:** DANGER!  
**Hazard Statements:** Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing genetic defects. Harmful to the aquatic environment with long lasting effects.

**Precautionary Statements:**  
**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection. Avoid release to the environment.

**Response:** If exposed or concerned: Get medical advice/attention. If swallowed: Rinse mouth. Do not induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store between 45-90°F (7-32°C).  
**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazards Not Otherwise Classified (HNOC)**

The above hazards are for the uncured Resin component of SET-XP. Upon combination with the Hardener component of SET-XP an innocuous solid is formed which does not present any immediate hazards. Upon grinding or cutting the cured product the following hazards may apply.



**Health Hazards:** Carcinogenicity Category 1A  
STOT, Repeated Exposure Category 2 (Lung)  
**Hazard Statements:** May cause cancer. May cause damage to organs (Lung) through prolonged or repeated exposure.  
**Precautionary Statements:** Do not breathe dust.

**3. Composition Information**

**General Information**

This product is a mixture. Hazardous ingredients for each component are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

**Resin (white side)**

Chemical Name	CAS Number	Weight %
Bisphenol A/Epichlorohydrin	25068-38-6	40-60
Phenol, polymer with formaldehyde, glycidyl ether	28064-14-4	40-60
Butyl Glycidyl Ether	2426-08-6	1-10
Titanium Dioxide	13463-67-7	1-10

**Hardener (black side)**

Chemical Name	CAS Number	Weight %
Silica, crystalline quartz	14808-60-7	20-30
Polyamido Amine	68953-36-6	10-20
2,4,6-Tris(dimethylaminomethyl)phenol	90-72-2	1-10
Dimethyl silicone polymer with silica	67762-90-7	1-10
Phenol	108-95-2	1-10
Benzene-1,3-Dimethanamine	1477-55-0	1-10
3,6,9-triazaundecamethylenediamine	112-57-2	1-5

**4. First-Aid Measures**

**General Information**

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

**Routes of Exposure**

**Eye Contact:** Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision, or swelling persists, **consult a physician.**

**Skin Contact:** Remove contaminated clothing and product, immediately wash affected area with soap and water. Do not apply greases or ointments. Chemical burns must be treated by a **physician.**

**Ingestion:** Rinse mouth immediately. Give large amounts of milk or water, if person is conscious. Only induce vomiting at the instruction of medical personnel. **Consult a physician.**

**Inhalation:** Remove patient to fresh air. Oxygen or artificial respiration if needed. If patient continues to experience difficulty breathing, **consult a physician.**

**Most Important Symptoms**

Irritant effects. Symptoms include itching, burning, redness and tearing. Burning pain and severe corrosive skin damage. Causes severe eye damage. May cause temporary blindness and severe eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause allergic skin reaction. Prolonged exposure may cause chronic effects.

**5. Fire-Fighting Measures**

**Suitable Extinguishing Media:** Extinguish with foam, carbon dioxide, dry powder, or water fog.

**Additional Information:** None known.

**Hazards during Fire-Fighting:** Hazardous decomposition products may occur when materials polymerize at temperatures above 500°F (260°C). Irritating and toxic gases/fumes may be released during a fire. Water run-off can cause environmental damage.

**Fire-Fighting Procedures:** Use standard fire-fighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

**6. Accidental Release Measures**

**Personal Precautions**

Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Local authorities should be advised if significant spillages cannot be contained.

**Clean-Up Methods**

**Small spills:** Wipe up with absorbent material (e.g. cloth, fleece). Place in leak-proof containers. Seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination.

**Large spills:** Stop the flow of material, if this is without risk. Dike far ahead of spill for later disposal. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Prevent entry into waterways, sewer, basements or confined areas.

**Environmental Precautions**

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment.

**7. Handling and Storage**

**Handling**

Mechanical ventilation or local exhaust ventilation is recommended. Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protective equipment. When using, do not eat, drink or smoke. Avoid contact with eyes, skin, and clothing. Pregnant women should not work with this product if there is risk of exposure. Observe good industrial hygiene practices.

**Storage**

Store in a closed container away from incompatible materials. Keep in original container. Store in a dry place out of direct sunlight. Keep out of the reach of children. Store between 45-90°F (7-32°C). Keep away from heat and sources of ignition.

**8. Exposure Controls / Personal Protection**

**Personal Protective Equipment**

**Protective Measure:** Wear appropriate personal protective equipment.  
**Eye Protection:** Wear chemical splash goggles or safety glasses with side shield.  
**Hand Protection:** Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.  
**Skin and Body Protection:** Wear long sleeve shirt/long pants and other clothing as required to minimize contact.  
**Respirator Protection:** The use of a respirator is not required during normal use of this product. If grinding or cutting cured product the use of an approved respirator is recommended.  
**General Hygiene:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**Engineering Controls**

When using indoors good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Ready access to running water is required. Provide eyewash station.

**Exposure Limits**

Component *Skin Designation	OSHA (PEL)	ACGIH (TLV)	NIOSH Pocket Guide
Quartz (14808-60-7)	0.3 mg/m <sup>3</sup> (total dust) 0.1 mg/m <sup>3</sup> (respirable)	0.025 mg/m <sup>3</sup> (respirable)	0.05 mg/m <sup>3</sup> (respirable)
Phenol* (CAS 108-95-2)	19 mg/m <sup>3</sup> 5 ppm	5 ppm	60 mg/m <sup>3</sup> (Ceiling) 15.6 ppm (Ceiling)
m-Phenylenebis(methylamine)* (CAS 1477-55-0)	N/E	0.1 mg/m <sup>3</sup> (Ceiling)	0.1 mg/m <sup>3</sup> (Ceiling)
N-Butyl Glycidyl Ether (2426-08-6)	270 mg/m <sup>3</sup> 50 ppm	3 ppm	30 mg/m <sup>3</sup> (Ceiling) 5.6 ppm (Ceiling)
Titanium Dioxide (13463-67-7)	5 mg/m <sup>3</sup> (respirable) 15 mg/m <sup>3</sup> (total dust)	10 mg/m <sup>3</sup>	N/E

**Additional Information**

**After Cure:** Product forms an innocuous solid. Processing after cure (grinding or cutting) may produce dust containing compounds that present an inhalation hazard.

**9. Physical and Chemical Properties**

<u>Property</u>	<u>Resin</u>	<u>Hardener</u>
<b>Physical State:</b>	Liquid, Paste	Liquid, Paste
<b>Color:</b>	White	Dark Green
<b>Odor:</b>	Sweet	Ammonia
<b>pH:</b>	6.9	10.3
<b>Flammability limit – lower %:</b>	No data	No data
<b>Flammability limit – upper %:</b>	No data	No data
<b>Vapor Pressure:</b>	Non-volatile	No data
<b>Vapor Density:</b>	No data	No data
<b>Solubility:</b>	Insoluble in water	Slightly soluble in water
<b>Freezing/Melting Point:</b>	No data	No data
<b>Boiling Point:</b>	> 500 °F (>260 °C)	No data
<b>Flash Point:</b>	250 °F (121 °C) Open Cup	262 °F (128 °C) Closed Cup
<b>Evaporation Rate:</b>	No data	No data
<b>Decomposition Temperature:</b>	No data	No data
<b>Specific Gravity:</b>	1.21 at 72°F (22°C)	1.59 at 72°F (22°C)
<b>VOC (after cure):</b>	3 g/L	3 g/L
<b>Kow:</b>	No data	No data
<b>Viscosity:</b>	No data	No data

# SET-XP® High Strength Anchoring Adhesive for Cracked and Uncracked Concrete

## SAFETY DATA SHEET



### 10. Stability and Reactivity

#### Resin (white side)

**Reactivity:** This product is stable and non-reactive under normal conditions.  
**Chemical Stability:** Stable under normal storage conditions.  
**Condition to Avoid:** High heat and open flame.  
**Substances to Avoid:** Oxidizing agents, acids, organic bases, and amines  
**Hazardous Reactions:** Hazardous polymerization does not occur.  
**Decomposition Products:** Carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

#### Hardener (green side)

**Reactivity:** This product is stable and non-reactive under normal conditions.  
**Chemical Stability:** Stable under normal storage conditions.  
**Condition to Avoid:** High heat and open flame.  
**Substances to Avoid:** Strong oxidizing agents. Peroxides. Phenols. Acids.  
**Hazardous Reactions:** Hazardous polymerization does not occur.  
**Decomposition Products:** Carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

### 11. Toxicological Information

#### Likely Routes of Exposure

**Ingestion:** May be harmful if swallowed. Ingestion may cause irritation to the gastrointestinal tract.  
**Inhalation:** May cause respiratory irritation  
**Skin contact:** Causes skin irritation. Causes severe skin burns. May cause an allergic skin reaction.  
**Eye contact:** Causes serious eye irritation. Causes severe eye damage.

#### Information on Toxicological Effects

**Acute toxicity:** Occupational exposure to the substance or mixture may cause adverse effects.

Product	Species	Test Result
SET-XP Resin (CAS mixture)	<b>Acute, Dermal</b> , LC50	Rabbit >2000 mg/kg
	<b>Acute, Oral</b> , LD50	Rat >5000 mg/kg
SET-XP Hardener (CAS mixture)	<b>Acute, Dermal</b> , LD50	Rabbit >2000 mg/kg
	<b>Acute, Oral</b> , LD50	Rat >5000 mg/kg

**Skin corrosion/irritation:** Causes severe skin burns.  
**Eye damage/eye irritation:** Causes severe eye damage.  
**Respiratory sensitization:** No data available.  
**Skin sensitization:** May cause an allergic skin reaction.  
**Germ cell mutagenicity:** Contains a component that is suspected of causing genetic defects.  
**Carcinogenicity:** May cause cancer. Quartz and Titanium Dioxide are considered carcinogens only in their inhalable form. Exposure to respirable Quartz and Titanium Dioxide is likely only when grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (14808-60-7) 1 Carcinogenic to humans.  
Titanium Dioxide (13463-67-7) 2B Possibly Carcinogenic to humans.  
Phenol (108-95-2) 3 Not classifiable as to carcinogenicity in humans.

#### NTP Report on Carcinogens

Quartz (14808-60-7) Known to be Human Carcinogen

**Reproductive toxicity:** The available data does not indicate that any ingredients of this product are reproductive toxins.  
**Aspiration hazard:** Not expected to be an aspiration hazard.  
**Specific target organ toxicity:**  
**Single exposure** No data available.  
**Repeated exposure** May cause damage to organs (lung) through prolonged or repeated exposure.

#### Further Information

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

**12. Ecological Information**

**General Information**

Information given is based on data on the components and the ecotoxicology of similar products. Resin is classified as toxic to aquatic life with long lasting effects. Hardener is classified as harmful to aquatic life with long lasting effects. Avoid release to the environment.

**Supporting Data**

Component	Species	Test Result
SET-XP Resin (CAS mixture)		
<b>Aquatic Acute</b> , Algae, EC50	Algae	>1000 mg/l, 72 hours
<b>Aquatic Acute</b> , Crustacea, EC50	Daphnia Magna	324.87 mg/l, 48 hours
<b>Aquatic Acute</b> , Fish, LC50	Fish	707.11 mg/l, 96 hours
Phenol (108-95-2)		
<b>Aquatic</b> , Crustacea, EC50	Daphnia	4.7-6.4 mg/l, 48 hours
<b>Aquatic</b> , Fish, LC50	Rainbow trout	7.5-14 mg/l, 96 hours

**Persistence and degradability:** This product is not expected to be readily biodegradable.

**Bioaccumulative potential:** No data available for this product.

**Partition coefficient n-octanol / water (log Kow)**

Butyl glycidyl ether (2426-08-6) 0.63

Phenol (108-95-2) 1.46

**Mobility in soil:** This product is non-volatile.

**Further Information**

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

**13. Disposal Consideration**

**Waste Disposal of Substance:** Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Container Disposal:** Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

**Disposal of Cured Product:** Grind or chip off surface. Solid material does not require special disposal.

**14. Transportation Information**

**Resin (white side)**

**UN number:** UN3082  
**UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A-Epichlorohydrin), 9, III, Marine Pollutant  
**Precautions:** Marine Pollutant  
**Required Labels:** 9  
**ERG Code (IATA):** 9L  
**EmS (IMDG):** F-A, S-F

**Hardener (black side)**

**UN number:** UN2735  
**UN proper shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S. (Benzene-1,3-Dimethaneamine), 8, II  
**Precautions:** Corrosive  
**Required Labels:** 8  
**ERG Code (IATA):** 8L  
**EmS (IMDG):** F-A, S-B

**Additional Information**

Check limited quantity regulations prior to shipping, SET-XP cartridges may qualify for LQ shipping exemptions.

**Special precautions for user:** Read safety instructions, SDS and emergency procedures before handling.

**SET-XP® High Strength Anchoring Adhesive for Cracked and Uncracked Concrete**  
**SAFETY DATA SHEET**



Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:

This substance/mixture is not intended to be transported in bulk

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

**15. Regulatory Information**

**United States**

**Federal Regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)** Not regulated.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)** Not listed.

**CERCLA Hazardous Substance List (40 CFR 302.4) :**

Phenol (108-95-2) LISTED

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

Hazard Categories:	Immediate	Delayed	Fire	Pressure	Reactivity
Resin	Yes	Yes	No	No	No
Hardener	Yes	Yes	No	No	No

**SARA 302 Extremely hazardous substance:** No

**SARA 311/312 Hazardous chemical:** Yes

**SARA 313 (TRI reporting):**

Chemical Name	CAS Number	% by weight
Phenol	108-95-2	1-10

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Phenol (108-95-2)

**US State Right-To-Know Lists**

Chemical	Massachusetts RTK	New Jersey Work and Community RTK Act	Pennsylvania Worker and Community RTK Law	Rhode Island RTK
Butyl glycidyl ether (CAS 2426-08-6)	Listed		Listed	
Titanium dioxide (CAS 1317-80-2)	Listed		Listed	
m-Phenylenebis(methylamine) (CAS 1477-55-0)	Listed		Listed	
Phenol (CAS 108-95-2)	Listed	Listed	Listed	Listed
Quartz (CAS14808-60-7)	Listed		Listed	

**US. California Proposition 65:** WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or reproductive harm.

Component	Regulation	% In Blend (approx.)	Remark
Titanium dioxide (CAS 13463-67-7)	ACGIH	1-10	Carcinogenic
Quartz (14808-60-7)	ACGIH	20-30	Carcinogenic
Carbon Black (1333-86-4)	ACGIH	< 0.1	Carcinogenic

**Canada**

This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR.

**SET-XP® High Strength Anchoring Adhesive for Cracked and Uncracked Concrete**  
SAFETY DATA SHEET



**WHMIS Classification**

<b>Class E: Corrosive</b>	<b>Class D-2A: Material Causing other toxic effects</b>

**International**

**International Inventories**


Country or Region	Inventory	On Inventory? (Yes/No)
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

**16. Other Information**

**Date Prepared or Revised:** December 2014  
**Supersedes:** September 2014  
**Contact Simpson Strong-Tie Environmental Health and Safety at** [EHS@strongtie.com](mailto:EHS@strongtie.com)

**Additional Resin (white side) Classifications**

**NFPA Ratings**




**HMIS Rating**

HEALTH HAZARD	2
FLAMMABILITY HAZARD	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

**Additional Hardener (green side) Classifications**

**NFPA Ratings**



**HMIS Rating**

HEALTH HAZARD	3
FLAMMABILITY HAZARD	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

**Abbreviations**

**ACGIH:** American Conference of Governmental Industrial Hygienists  
**CAS No.:** Chemical Abstract Service Registry Number  
**CERCLA:** Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)



# SET-XP® High Strength Anchoring Adhesive for Cracked and Uncracked Concrete

## SAFETY DATA SHEET



<b>CPR:</b>	Controlled Product Regulations (Canada)
<b>DOT:</b>	Department of Transportation (U.S.)
<b>EPA:</b>	Environmental Protection Agency (U.S.)
<b>GHS:</b>	Globally Harmonized System of Classification and Labeling of Chemicals
<b>HEPA:</b>	High-Efficiency Particulate Air
<b>HMIS:</b>	Hazardous Materials Identification System
<b>IARC:</b>	International Agency for Research on Cancer
<b>IATA:</b>	International Air Transport Association
<b>IMDG:</b>	International Maritime Dangerous Goods code
<b>LPP:</b>	Limité Permissible Ponderado (Chile)
<b>NIOSH:</b>	National Institute of Occupational Safety and Health (U.S.)
<b>NFPA:</b>	National Fire Protection Association (US)
<b>NTP:</b>	National Toxicology Program (US)
<b>OSHA:</b>	Occupational Safety and Health Administration (U.S.)
<b>PEL:</b>	Permissible Exposure Limit
<b>SARA:</b>	Superfund Amendments and Reauthorization Act (U.S. EPA)
<b>SDS:</b>	Safety Data Sheet
<b>STEL:</b>	Short Term Exposure Limit (15 minute Time Weighted Average)
<b>STOT:</b>	Specific Target Organ Toxicity (GHS Classification)
<b>TLV:</b>	Threshold Limit Value
<b>TSCA:</b>	Toxic Substances Control Act (U.S.)
<b>TWA:</b>	Time Weighted Average (exposure for 8-hour workday)
<b>U.S.:</b>	United States
<b>VOC:</b>	Volatile Organic Compounds
<b>WHMIS:</b>	Canadian Workplace Hazardous Materials Information System

### Disclaimer

This Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© 2014 Simpson Strong-Tie Company Inc.

### Internal

#### FOR INTERNAL USE ONLY

SET-XP Resin:  
XCOM3B – 50% Cartridge

SET-XP Hardener:  
XCOM3B – 50% Cartridge  
XCORR – 50% Cartridge